



GASOLINE STERNDRIVE ENGINE DRIVES AND RATIOS

P	= Primary Ratio	Most often used in applications below 5000 feet
O	= Optional Ratios	Alternate gear ratios for use below 5000 feet
H	= High-Altitude Ratios	Ratios only to be used above 5000 feet

MerCruiser Series	HP	Base Engine	Fuel System	Max RPM (x 1000)	Alpha					Bravo One			Bravo Two			Bravo Three			
					1.47	1.62	1.81	2.0	2.4	1.36	1.5	1.65	1.81	2.0	2.2	1.81	2.0	2.2	2.43
Sterndrive	135	3.0L	2V Carb	44-48	--	--	--	P	H	--	--	--	--	--	--	--	--	--	--
	190	4.3L	2V Carb	44-48	--	O	P	H	--	--	--	--	O	P	--	--	O	P	
	220	4.3 MPI	MPI	44-48	O	P	H	--	--	--	--	--	O	P	--	--	P	O	
	220	5.0L	2V Carb	44-48	--	P	H	--	--	--	O	P	--	O	P	--	--	P	H
	250	5.7L	2V Carb	44-48	O	P	H	--	--	--	O	P	--	--	--	--	O	P	H
	260	5.0 MPI	MPI	46-50	O	P	H	--	--	--	O	P	--	O	P	--	O	P	H
	300	350 MAG MPI	MPI	46-50	P	H	--	--	--	O	P	H	O	P	H	O	P	H	--
	300	350 MAG MPI Horizon	MPI	46-50	--	--	--	--	--	O	P	H	O	P	H	O	P	H	--
	320	MX 6.2 MPI	MPI	48-52	--	--	--	--	--	O	O	P	--	O	P	--	O	P	H
	320	MX 6.2 MPI Horizon	MPI	48-52	--	--	--	--	--	O	O	P	--	O	P	--	O	P	H
	375	496 MAG	MPI	44-48	--	--	--	--	--	O	P	H	P	O	H	P	O	H	--
	425	496 MAG High Output (1) (2) (3)	MPI	46-50	--	--	--	--	--	O	P	H	P	O	H	P	O	H	--

Notes:

- (1) Bravo One XR™ drive is optional factory upgrade
- (2) Bravo One XR available in 1.5:1, 1.35:1 and 1.26:1 ratios
- (3) 496 MAG™ High Output models paired with Bravo® X version of Bravo One®, Two® or Three® drives